



## Flexible and rugged family of hand-held scanners ideal for tough industrial environments

The LS3400 Scanner family consists of four rugged scanners rated at IP65 and suited to scanning 1D barcodes in industrial environments.

LS3408ER: This extended range tethered laser scanner has an exceptionally wide working range from 10cm (4 in) to 14.6m (45 ft).

LS3408FZ: Fuzzy logic technology allows this tethered laser scanner to read dirty, damaged or poorly printed barcodes from 10cm (4 in) to 213.4cm (84 in).



### Features & Benefits

#### LS3408ER - Flexible working range up to 13.7 meters (45 feet)

- Rugged ergonomic IP65 sealed industrial design
- Bright laser diode ensures precise aiming at long distances
- Multiple on board interfaces ensure connectivity to existing devices.

#### LS3408FZ - Fuzzy logic improves barcode scanning performance

- Ergonomic rugged design withstands multiple 2 meters (6.5 feet) drops to concrete
- Supports Reduced Space Symbologies (RSS)
- Multiple connectivity options ensure plug and play functionality



# LS3400 Laser Scanner Family

## Specifications\*



### PHYSICAL CHARACTERISTICS (ALL MODELS)

- Dimensions: 18.65 cm H x 12.25 cm W x 7.43 cm 7.34 in. H x 4.82 in. W x 2.93 in. D
- Weight (without cable): 356 gm/12.56 oz.
- Power Requirements: 4.5 – 14VDC
- Stand-by Current: 50mA
- Power Sources: Depending on host:
  - Host power
  - External power supply
- Color: Twilight Black/Yellow

### PERFORMANCE CHARACTERISTICS (ALL MODELS)

- Scanner type: Retrocollective
- Light source: 650 nm visible laser diode
- Scan repetition: 36 scans per second typical
- Print Contrast: 25% minimum reflective difference
- Decode Capability: UPC.EAN, UPC.EAN with Supplemental, UCC.EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar

- (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants
- Interfaces Supported: RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation, IBM 468X/469X, USB and Synapse

### USER ENVIRONMENT (ALL MODELS)

- Humidity: 5% to 95% relative humidity, noncondensing
- Sealing: Sealed to IP65 specifications
- Drop specifications: Unit functions normally after repeated 6.5ft (2m) drops to concrete

### REGULATORY (ALL MODELS)

- Input transient protection: IEC 1000-4-(2,3,4,5,6,11)
- EMI/RFI: FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive,
- Japan VCCI/MITI/Dentori
- Laser safety: IEC825-1 Class 2

\*Specifications are subject to change without notification.

### DECODE ZONE (PER MODEL)



	LS3408	FZ LS3408
<b>Operating Temperature</b>	-30° to 50°C (-22° to 122°F)	-30° to 50°C (-22° to 122°F)
<b>Storage Temperature</b>	-40° to 70°C (-40° to 158°F)	-40° to 70°C (-40° to 158°F)
<b>Ambient Light Immunity</b>	Indoor: 450 ft. candles/ Indoor: 4,842 LUX	Indoor: 450 ft. candles/ 4,842 LUX
<b>Outdoor:</b>	Outdoor: 8,000 ft. candles/86,080 LUX	Outdoor: 4,000 ft. candles/43,040 LUX
<b>Electrostatic discharge</b>	Conforms to 20 kV air discharge and 8 kV of contact discharge	Conforms to 20 kV air discharge and 8 kV of contact discharge

Psion Teklogix™ is a trademark of Psion Teklogix Inc. Other product names mentioned in this document may be trademarks of Psion Teklogix Inc. or trademarks or registered trademarks of other hardware, software, or service providers and are used herein for identification purposes only.

Windows and the Windows Logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.

\* Specifications are subject to change without notice.